



Lubricants – Specialty Oils

Version: 504/03

LHM Plus Fluid

Special hydraulic oil for power steering/brake system booster of Citroën.

Valvoline LHM Plus Fluid is a special fluid with improved flow at low temperatures to meet Citroën specifications for the hydraulic system, power steering/brake system booster and levelling system. The product has an extremely high and stable viscosity index and a very low pour point.

Performance levels
AFNOR NF R 12-640
ISO 7308
PSA (Citroën) B71 2710

Applications

Suitable for hydraulic steering/brake booster system of Citroën.

Suitable for hydraulic leveling system of Citroën.

Truck hydraulic cabin tilt system.

Hydraulic brake system of some agricultural equipment.

Features & Benefits

Superior performance

Valvoline LHM Plus is formulated with premium quality mineral base oil and specially selected additives to guarantee a very low pour point, excellent oxidation stability and good flow characteristics.

Superior protection

Valvoline LHM Plus Fluid provides good protection against wear, corrosion, foaming, and sludge building.

Consistent viscosity

Excellent viscosity-temperature properties at very high and very low temperatures. Stable viscosity over a long period.

Severe working conditions

Valvoline LHM Plus Fluid will also perform excellent under unfavorable working conditions, like driving in mountain areas.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline LHM Plus Fluid	
Viscosity, mm ² /s @ 100 °C. ASTM D-445	6,2
Viscosity, mm ² /s @ 40 °C. ASTM D-445	18,2
Viscosity Index ASTM D-2270	339
Viscosity, mm ² /s @ -40 °C. ASTM D-5293	125
Pour Point, °C ASTM D-5949	-60
Specific Gravity @ 15.6°C. ASTM D-4052	0,835
Flash Point, COC, °C. ASTM D-92	125

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 504/02

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.