

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants – Transmission Oils - Automotive

Version: 228/01

SynPower™ ATF +4

Premium fully synthetic ATF recommended by Valvoline for Chrysler and other automatic transmissions.

SynPower ATF + 4™ is a uniquely blended automatic transmission fluid that meets Chrysler Material Standard MS-9602. It is designed as a factory fill fluid for all 1998 and later Chrysler Corporation automatic transmissions and transaxles.

Approvals/Performance levels

Chrysler MS9602 (ATF +4)®
Chrysler MS7176E (ATF +3)®
Chrysler MS7176D (ATF +2)®
Chrysler MS7176 (ATF +)®
Recommended for use where Fiat 9.55550-AV4 is specified

Applications

Recommended for Chrysler automatic transmissions where ATF +4, +3, +2, +, are specified.

Suitable for use in some models of: Dodge, Fiat, Jeep, Hyundai, and Mitsubishi where these specifications are recommended.

London taxis.

Features and Benefits

Superior protection

Optimum protection against wear and tear, also under high stress working conditions.

Advanced additives

Advanced additives protect against corrosion, oxidation, foaming, and deposits.

Breakdown resistance

Premium synthetic base oils, balanced additive system avoid breakdowns and stick-slip even after long-time use.

Consistent, stable viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity over a long period.

Enhanced friction properties

Premium fully synthetic base oils, viscosity index improvers, and friction modifiers result in outstanding friction properties for smoother shifting. In addition, the product resists aging and has excellent thermal stability.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SynPower ATF 134	
Colour	Red
Viscosity, mm ² /s @ 100 °C. DIN 51562-1	7.55
Viscosity, mm ² /s @ 40 °C. DIN 51562-1	34.1
Viscosity Index DIN ISO 2909	198
Pour Point, °C DIN ISO 3016	-48
Specific Gravity @ 15.6°C. DIN 51757	0.848
Flash Point, COC, °C. DIN ISO 2592	196

This information only applies to products manufactured in the following location(s):
Europe

People Who Know Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces –

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2012, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.